

Louisiana State University Design Standards

DIVISION 12 - FURNISHINGS

1 WINDOW TREATMENTS

1.1 Blinds

1.1.1 All blinds shall have a lifetime warranty on working mechanisms.

1.1.2 Slat Requirements

1.1.2.1 No smaller than .006 gauge will be accepted

1.1.2.2 Only 25 millimeter or larger slat width will be accepted. Aluminum slats only - no vinyl slats accepted.

1.1.2.3 Spacing between slats shall be no greater than 21.5 millimeters

1.1.3 Head rail metal thickness must be .025 gauge or greater

1.1.4 Approved manufacturers are: Hunter Douglas-Dacor, Levalor-Riviera or equal (Prior approval by Planning, Design & Construction required for "equal").

1.2 Roller Shades

1.2.1 All shades shall have a lifetime warranty on working mechanisms.

1.2.2 Manually operated sunscreen roller shades with drive chain.

1.2.2.1 Drive Chain: #10 qualified stainless steel chain rated to 90 lb. (41 kg) minimum breaking strength. Nickel plate chain shall not be accepted.

1.2.3 Visually transparent single-fabric vinyl shade cloth.

1.2.3.1 Maximum 5 percent open

1.2.4 Provide shade hardware allowing for the removal of shade roller tube from brackets without removing hardware from opening and without requiring end or center supports to be removed.

1.2.5 Provide shade hardware that allows for removal and re-mounting of the shade bands without having to remove the shade tube, drive or operating support brackets.

1.2.6 Provide for universal, regular and offset drive capacity, allowing drive chain to fall at front, rear or non-offset for all shade drive end brackets. Universal offset shall be adjustable for future change.

1.2.7 Provide hardware capable for installation of a removable fascia, for both regular and/or reverse roll, which shall be installed without exposed fastening devices of any kind.

2 FURNITURE

2.1 Tablet Arm Chairs

2.1.1 Approximately ten percent (10%) of all fixed table arm auditorium or classroom seats in each room shall be left handed.